



版权归上海奉申制冷控制器股份有限公司










(1): Common contact
(1)-(3): Open on pressure rise
(1)-(5): Open on pressure drop

ELECTRICAL RATING			
Rated Amps./A \ Rated Voltage/V		A.C.110	A.C.220
Non-Inductive Current		24	16
Inductive Current	Full Load (FLA)	24	16
	Locked Rotor (LRA)	144	96



受控文件

Specifications

- Type: Auto reset
- Differential: Adjustable
- Configuration: Single
- Contact configuration: SPDT
- Degree of protection: IP44 with top cover
  IP20 without top cover
- Method of mounting control: Independently mounted
- Ambient working temperature: -40T65℃
  Intended transportation conditions: -40T65℃，≤85%RH (non condensing situation)
- Max refrigerant temperature: 120℃
- Mechanical life:300,000 Times

MODEL	PRESSURE RANGE [barg]/[psig]	DIFF.RANGE [bar]/[psi]	FACTORY SETTING					
			CUT OUT [barg]/[psig]	CUT IN [barg]/[psig]	DIFF. [bar]/[psi]	Use terminals	Max.PS [barg]/[psig]	Burst Pressure [barg]/[psig]
PX6E	-0.3~7 / -4~102	0.6~4 / 9~58	2±0.2 / 29±2.9	3±0.3 / 43±4.3	1±0.15 / 14±2.2	1-5	17 / 246	80 / 1160

Mark	No.	Changed no.	Sign	Date	Single Pressure Control PX6E			Art. NO.	PX6E-00-00-01
Design			Standard		Specification			Code	
Check					Marking of drawing	Qty	Scale	Material	
Approve			Date	2021.12	Total Page	Page		Shanghai Fengshen Refrigeration Controls.Co,Ltd	